COLOMBO SCIENTIFIC PUBLISHING

INTERNATIONAL JOURNAL OF COMPUTER SCIENCE & INFORMATION SYSTEM
E-ISSN: 2536-7919
P-ISSN: 2536-7900
PAGE NO: 164-177

Remotely Configurable Client-Side Logging as a Mechanism for Improving the Observability of Large-Scale iOS Applications

Maksim Bezdenezhnykh
Independent Researcher Dubai, UAE

ARTICLE INFO

Article history:
Submission: December 14, 2025
Accepted: January 12, 2026
Published: January 31, 2026
VOLUME: Vol.11 Issue 01 2026

Keywords:
iOS, observability, remote configuration, client-side logging, structured logging, feature flags, mobile telemetry, privacy by design, Swift, release engineering.

ABSTRACT

Diagnosing defects in large iOS applications is usually bound to the release cycle: to collect additional evidence from affected users, engineers add logging code, ship a build, pass App Store review and wait until users update. This article examines remotely configurable client-side logging, in which the composition and verbosity of collected data are defined on a server, as a way to separate diagnostic observability from releases. The aim is to systematize the engineering requirements for such logging and to propose a reference model for large iOS applications. The methodology combines an integrative review of 22 peer-reviewed and industry sources published from 2020 to 2025, comparative analysis of logging, feature flag and safe deployment practices, conceptual modeling and an anonymized reflective case of a large live streaming application. The results include a four-layer reference architecture, a configuration schema with safety bounds, a policy lifecycle with fail-safe defaults and a decision matrix. Remote configuration shortens the diagnostic loop when governed by expiration, resource budgets and redaction rules. The findings will interest mobile engineers, architects and engineering managers.

1. INTRODUCTION

Mobile applications have become a routine channel for retail, travel, media consumption and payments, and the reliability of the client software now affects measurable economic activity. According to a study by Burley and Fradkin [1], the App Store ecosystem in the United States facilitated 406 billion US dollars in billings and sales in 2024, compared with 142 billion US dollars in 2019, and apps from US developers were downloaded 12.4 billion times worldwide in 2024, 36% more than in 2019 [1]. When an application that mediates such transactions fails on a subset of devices, the engineering team needs evidence from those devices, and that evidence has to be collected without harming the experience of users who are not affected.

The technical base of iOS applications has also become more heterogeneous. Baresi et al. [2] analyzed 140 open-source native iOS applications and found that 94% of them contain Swift code, that SwiftUI appears in 64 of them, and that almost half of the applications started after the release of SwiftUI adopted it from the beginning. Large commercial code bases typically keep Objective-C modules and UIKit screens next to Swift, SwiftUI and Combine code, so any diagnostic mechanism has to work across languages, UI frameworks and team boundaries. At the same time, mobile devices impose resource limits that server software does not face. Hort et al. [3] reviewed 156 publications on performance optimization for mobile applications and found that energy consumption receives more research attention than any other performance characteristic; network activity, memory and responsiveness are also treated as constrained resources, and additional instrumentation consumes all of them.

Logging research explains why diagnostic data is difficult to plan in advance. In a systematic mapping of 108 studies, Cândido et al. [4] report that developers decide where and what to log largely by experience and trial and error, that excessive logging degrades performance and raises storage costs, and that insufficient logging leaves operations teams without usable evidence. Chen and Jiang [5] surveyed 69 papers on log instrumentation and describe the same tension between diagnosability and overhead, together with remedies such as sampling and cost-aware selection of logging points. He et al. [6] show how automated log analysis depends on the quality of the logs that instrumentation produces.

Research on observability, however, concentrates on server infrastructure: the surveys of Usman et al. [7] and Gomes et al. [8], the latter covering 66 studies published from 2019 to 2024, address microservices, containers and edge infrastructure, while the client application on the user's device remains outside their scope.

Studies of mobile software confirm that client-side diagnostics are weakly maintained and that external reports rarely compensate for this. Harty et al. [9] found that only 1.35% of commits in 57 open-source Android applications changed mobile analytics logging statements, compared with about 10% of commits that changed traditional logging statements in an earlier study. Johnson et al. [10] examined 180 reproducible Android bug reports: 54 of them contained no environment information, and 92.2% missed one or more steps needed for reproduction. In practice, this combination forces a familiar sequence. To learn more about a defect that affects part of the audience, engineers add log statements, build a release, submit it for review, release it, and wait until enough affected users update and encounter the defect again. The sequence can take days or weeks because each step has its own queue, and the information gained is fixed in the binary until the next release.

Server-side engineering has long separated runtime behavior from deployment through configuration and feature flags. Mahdavi-Hezaveh et al. [11] analyzed 99 grey literature artifacts and 10 peer-reviewed papers, surveyed practitioners from 38 companies and identified 17 feature toggle practices in four categories: management, initialization, implementation and clean-up. Meinicke et al. [12] show that feature flags are expected to be temporary and require planned removal, whereas configuration options tend to remain permanently. Rahman [13] found 3.1 thousand toggles across 38 components of Chromium. These studies treat flags primarily as switches for product functionality. The use of the same mechanism to control what the client records, how verbosely and for whom, has received little systematic attention, although it raises its own questions of privacy, resource cost and failure behavior.

The privacy dimension is not hypothetical. Lyons et al. [14] collected logs from 1,214 Android devices and detected one or more types of personally identifiable information on 94.1% of them. Xiao et al. [15] tested 5,102 iOS applications and found 3,423 whose App Store privacy labels did not match their observed data practices, while Kollnig et al. [16] showed that 80.2% of iOS applications claiming to collect no data still contained one or more tracking libraries. Aghili et al. [17] analyzed 25 public log datasets and surveyed 45 practitioners to clarify which log attributes require anonymization. A mechanism that can change the content of client logs without a new binary therefore has to carry its own privacy controls. Configuration changes are also a known source of incidents in large services [18], and safe deployment systems such as the one described by Li et al. [19] show that staged exposure guided by telemetry can catch harmful changes before they reach the whole population.

The research gap can be stated as follows: the literature offers mature results on log instrumentation, feature flag governance, safe deployment and log privacy, but it does not integrate them into a model of remotely configurable logging for mobile clients, where verbosity control, cohort targeting, resource budgets, privacy filtering and behavior under unavailable configuration must be decided together. The aim of this study is to systematize the engineering requirements for remotely configurable client-side logging in large iOS applications and to propose a reference model that supports these decisions. The scientific novelty of the study consists in a reference model that links configuration governance practices from feature flag research and safe deployment systems with mobile resource budgets and privacy filtering, and expresses them as explicit decision points with default values for iOS applications. The author's hypothesis is that separating the composition and verbosity of client logs from the binary release, under explicit expiration, resource budgets, privacy filters and fail-safe defaults, reduces the diagnostic loop from the scale of the release cycle to the scale of configuration propagation without a proportional increase in device resource consumption or privacy exposure.

The study has several limitations that define its scope rather than weaken its conclusions. It is conceptual and does not report controlled measurements; the practical case is anonymized and described qualitatively; part of the privacy evidence comes from the Android ecosystem and is used as an indicator of logging behavior in mobile software generally; and platform interfaces evolve, so the model is formulated at the level of mechanisms rather than specific API versions.

The practical value of the work lies in a set of decisions that iOS teams can apply when they design or audit diagnostic infrastructure, and in a vocabulary that helps engineering managers, privacy officers

and release managers discuss these decisions. For the United States the topic has a direct economic dimension: the US App Store ecosystem nearly tripled from 2019 to 2024 [1], and a large share of this activity passes through client applications whose failures are diagnosed by mobile engineers. The author's professional field, iOS engineering in Swift and Objective-C with UIKit, SwiftUI and Combine, media playback and client observability in large distributed teams, practiced since 2019, addresses precisely this layer, and the transfer of such practice into documented, reproducible engineering methods can support the reliability of US consumer software and the training of engineers who build it.

Materials and Methods

The study follows a qualitative, design-oriented research strategy that moves from evidence to a model and then tests the model for plausibility against practice. Four methods were combined: an integrative literature review, a comparative analysis of practices, conceptual modeling and a practice-based reflective case.

The integrative review covered peer-reviewed publications and recognized industry studies published from 2020 to 2025. Searches were run in IEEE Xplore, the ACM Digital Library, SpringerLink, ScienceDirect, PeerJ and the USENIX proceedings with combinations of the terms "logging", "log instrumentation", "observability", "mobile", "iOS", "Android", "feature toggle", "feature flag", "configuration", "safe deployment", "sampling", "tracing", "privacy" and "sensitive information". Preprints were included only when a peer-reviewed version could be identified, and in that case the peer-reviewed version is cited. Blogs, vendor marketing pages, press releases and news articles were excluded. A source entered the corpus when it reported empirical evidence or a design that bears on one or more of five questions: what to log on the client, how to change logging at runtime, how to limit its cost, how to protect personal data in logs and how to make configuration changes safe.

The source base was classified into five groups. The first group consists of surveys and mapping studies that provide the theoretical frame for logging and observability [3-8]. The second group consists of empirical studies of mobile logging, privacy and diagnostics, which supply quantitative evidence about client behavior [2, 9, 10; 14-17]. The third group covers feature flag and configuration research [11-13], which provides the governance practices transferred into the model. The fourth group includes systems papers on safe deployment, configuration risk, tracing and instrumentation overhead [18-22], which supply mechanisms for staged exposure, retroactive capture and cost control. The fifth group is the industry study of the US App Store ecosystem [1], used for the market context in the Introduction. Apple developer documentation for unified logging, background transfers, diagnostic reporting and App Store privacy details was consulted to keep the model consistent with platform conventions; these mechanisms are described at the level of their documented purpose.

The comparative analysis evaluated the practices found in the corpus against five criteria: granularity of control (global, per category, per cohort, per session), propagation latency of a change, safety mechanisms (defaults, expiration, validation, rollback), resource cost on the device and privacy controls. The results of this comparison are summarized in Table 1 in the next section, where each finding is paired with a design implication.

Conceptual modeling translated the design implications into four artifacts: a layered reference architecture, a configuration schema with recommended defaults and safety bounds, a policy lifecycle with fail-safe transitions and a decision matrix for typical diagnostic situations. Each element of these artifacts is traced to the sources that motivate it, and each table and figure carries a note on the sources used.

The reflective case draws on the author's engineering practice on a large live streaming application with a multimillion audience, where the author took part in introducing remotely configurable client-side logging and in architecture reviews within a large distributed iOS team. The case is fully anonymized: the article does not name the employer, the product or internal systems and does not report internal metrics. No user data was collected for this study. The case is used in two ways: to check whether each element of the model corresponds to a decision that a real team has to make, and to formulate conditions under which the recommendations apply. It is not treated as a measured experiment, and all quantitative statements in the article come from the cited sources.

Results and Discussion

The first result of the analysis is a decomposition of the diagnostic loop for client defects. The loop begins when a signal indicates that a defect exists (a crash report, a support ticket, a drop in a business metric) and ends when engineers hold enough evidence to identify the cause. In a release-coupled organization the evidence that can be collected is fixed at build time. If the existing logs are insufficient, the team has to extend the instrumentation in code, merge the change, build and test a release candidate, pass App Store review, expose the release to users, wait until affected users install it and encounter the defect again, and only then receive the new data. Every stage has an independent queue, and the last two stages depend on user behavior that the team cannot control. The bug report study by Johnson et al. [10] shows why the loop is so often entered: external reports frequently lack environment details and reproduction steps, so engineers cannot reproduce the defect locally and need data from the field.

Remotely configurable logging changes the structure of the loop rather than the speed of individual steps. The instrumentation points already exist in the binary at a low verbosity, and a server-side policy decides which categories are recorded, at what level, for which cohort and for how long. A diagnostic request then requires authoring and approving a policy, propagating it to the targeted devices and waiting for the defect to recur, after which the data is uploaded under the limits set by the same policy. The comparison of the two loops is shown in Figure 1, because the difference lies in which stages are present at all, and a diagram makes this easier to see than a list.




Figure 1. Release-coupled and remotely configured diagnostic loops for an iOS application (compiled by the author based on [10, 11, 19])

Figure 1 shows that the remotely configured loop removes the code change, the build, the store review and the update adoption stages from the path of a diagnostic request. Two stages remain that depend on the outside world: propagation of the policy, which is bounded by how often clients fetch configuration, and recurrence of the defect, which no diagnostic technique can shorten. The loop also acquires a new stage, policy approval, which carries the governance burden that was previously spread across code review and release management. The model developed below is largely a specification of what this approval stage must check.

The literature reviewed in this study provides the basis for those checks. Table 1 summarizes the findings that the comparative analysis selected as directly relevant to client logging and pairs each one with the design implication used in the model. A table is used because the reader needs to see the line from evidence to decision for each element, and the same structure later allows the elements of the model to be traced back to their sources.

Table 1. Evidence base of the study and design implications for remotely configurable logging (compiled by the author based on [3-5; 17-21])

Established finding	Design implication
Developers choose where and what to log by experience; too little logging hampers diagnosis, too much adds overhead, storage cost and noise	Verbosity is controlled per category at runtime rather than fixed at build time
Only 1.35% of commits changed mobile analytics logging, against about 10% for traditional logging	Stable instrumentation points in code are separated from frequently changing policies on the server
54 of 180 Android bug reports had no environment information; 92.2% missed one or more reproduction steps	Policies capture environment context and the order of events in complete sessions
17 toggle practices in four categories; default values, metadata and change logs are common; flags are temporary and their removal is a recurring problem	Owner, reason, default and expiration time are mandatory policy fields; every change enters an audit log
Correlated configuration changes cause disruptions in large services; telemetry-guided staged deployment reached 92.4% precision and 100% recall for data plane rollouts	Policies are validated, exposed in stages and stopped automatically by health signals
Head sampling misses rare edge cases; retroactive retrieval after symptoms preserves detail at low cost; low sampling rates can drop important events	Detailed events stay in a memory ring buffer and persist on triggers; cohorts are sampled instead of events
Energy is the dominant optimization target for mobile applications; deactivated instrumentation still cost 3.28 µs per call on a desktop processor and 14.29 µs on a Raspberry Pi 4	Disabled events cost one integer comparison; processing and upload are moved off interaction-critical paths and limited by budgets
Personal data was found in the logs of 94.1% of 1,214 devices; anonymization choices depend on attribute type and regulation	Each field carries a privacy class at the call site; only allowlisted fields are uploaded
3,423 of 5,102 iOS applications had privacy labels inconsistent with behavior; 80.2% of applications declaring no data collection contained tracking libraries	Approval of verbose policies includes a check against declared data practices

Read together, the rows of Table 1 point to a consistent conclusion. The evidence on logging practice shows that teams cannot predict which data they will need, which argues for runtime control. The evidence on feature flags and configuration risk shows that runtime control without ownership, expiration and staged exposure produces its own failures. The evidence on resource cost and privacy shows that every increase in verbosity has a price on the device and a potential cost for the user. Remotely configurable logging is therefore a governed capability rather than a single switch, and its design has to address all three groups of findings at once.

Reference architecture of remotely configurable logging

The second result is a reference architecture with four layers, shown in Figure 2. The architecture is organized by responsibility, so that each layer can be owned by a different team in a large organization and evolve at its own pace. Figure 2 is placed here because the remaining results (the schema, the lifecycle and the decision matrix) refer to these layers by name.




Figure 2. Four-layer reference architecture of remotely configurable client-side logging for iOS (compiled by the author based on [5, 17, 19, 20])

The instrumentation layer is a single logging interface used by all modules, written in Swift and exposed to Objective-C, so that legacy and new code record events in the same format. Each event belongs to a named category (for example, playback, networking, authentication), carries a level, a short static message and a set of typed fields, and every field is annotated with a privacy class at the call site. Static messages and typed fields make the logs structured at the source, which removes the need for the log parsing step that automated log analysis otherwise requires [6]. Messages and fields are evaluated lazily, so that a disabled event costs only a comparison of integers. This matters because instrumentation has a measurable cost even when monitoring is deactivated: Reichelt et al. [21] measured 3.28 microseconds per call for deactivated OpenTelemetry instrumentation on a desktop processor and 14.29 microseconds on a Raspberry Pi 4, a resource-constrained device. The same interface forwards events to unified logging for local debugging, which keeps the console experience familiar to engineers.

The on-device policy layer holds the active policy and answers one question for each event: should it be recorded, and where. It maps categories to levels, applies cohort membership, maintains a fixed-size ring buffer in memory for retroactive capture and enforces the budgets of the policy. Changes of the active policy are published as a stream of values, for which Combine is a natural fit in an iOS code base, so that interested components, including SwiftUI and UIKit diagnostic screens, react without polling. The idea of retroactive capture is taken from Hindsight, the tracing system of Zhang et al. [20], which retrieves detailed trace data lazily, only after a symptom of a problem has been detected; on a mobile client, the analogue is to keep detailed events in memory and persist them only when a trigger such as an error, a playback stall or a watchdog timeout fires.

The transport layer applies redaction according to the privacy classes, batches and compresses events, persists them in a bounded on-disk queue and uploads them under the conditions set by the policy, for example only on an unmetered network or while charging. Uploads are delegated to background transfer facilities of the operating system so that they survive suspension of the application. When the queue reaches its limit, events of low levels are dropped first, starting with the earlier ones, and the drop is itself counted, so that the server can tell missing data from absent events.

The control plane runs on the server. It stores policies, evaluates targeting rules, signs and versions policies, records every change in an audit log and exposes policies to clients through a lightweight endpoint. It also enforces governance: each policy has an owner, a reason linked to a ticket and an

expiration time. Exposure grows in stages, and health signals from the targeted cohort (crash rate, energy-related diagnostics, upload volume) can stop or revert a policy automatically, following the logic of staged, telemetry-guided deployment described by Li et al. [19], whose system reported a precision of 92.4% with a recall of 100% for data plane rollouts in a large cloud infrastructure.

Configuration schema and safety bounds

The third result is a configuration schema that turns the architecture into concrete decisions. Table 2 lists the parameters of a logging policy, their purpose, the default that the client applies when the parameter is absent and the bound that the client enforces regardless of what the server sends. The table format suits this content because engineers use it as a checklist when they implement or review the schema.

Table 2. Parameters of a remotely configured logging policy with client defaults and client-enforced bounds (compiled by the author based on [5, 11, 12, 14, 19, 20])

Parameter	Purpose	Client default when absent	Bound enforced by the client
Policy identifier and version	Identification and ordering of policies	Policy rejected	Version must be greater than the active one
Owner and reason (ticket reference)	Accountability and later review	Policy rejected	Both fields non-empty
Time to live, counted from fetch	Bounded lifetime of the policy	Policy rejected	Compiled maximum per level, for example 24 hours for debug level
Cohort rule (hashed bucket range, app version, OS version, device class, region)	Selection of installations	No installation targeted	Compiled cap on the share of installations; single-installation sessions only with user consent
Category levels	Verbosity per category	Baseline: error and warning	Debug level allowed only with a short time to live
Capture mode	Streaming or retroactive ring buffer	Ring buffer	Compiled cap on buffer size in memory
Triggers	Conditions that persist the buffer	Error, abnormal termination at next launch	Limit on persisted buffers per session
Budgets (bytes per session and per day, share of verbose time)	Resource limits on the device	Small baseline budget	Exceeding a budget returns the client to the baseline
Upload conditions	Network type, power state, deadlines	Unmetered network or charging	Queued data expires together with the policy
Field allowlist	Fields that may leave the device	Public fields only	Fields of the personal class are never uploaded in clear form
Kill switch	Immediate revocation	Off	Overrides every other parameter and purges queued verbose data

Two principles run through Table 2. The first is that the client is the final authority over its own safety: the server may request a verbose level for a category, but the client caps the duration, the volume and the cohort size and rejects any policy that falls outside its compiled bounds. This reflects the observation of Mehta et al. [18] that configuration changes in large services frequently need to be coordinated with other changes, and that errors in such changes are hard to catch in review. The second principle is that governance metadata is part of the schema, not an optional annotation. Mahdavi-Hezaveh et al. [11] report that setting default values, documenting toggle metadata and logging changes are common practices among practitioners, while clean-up practices such as adding expiration dates are reported less often. Making the expiration time and the owner mandatory fields moves clean-up from a matter of discipline to a property enforced by the client.

The schema also distinguishes cohort-level sampling from event-level sampling. Chen and Jiang [5] warn that low sampling rates can drop important events. For diagnostics, the model therefore selects a cohort of installations by a stable hashed bucket and records complete sessions for that cohort, rather than recording a random fraction of events from every device. A complete session from fewer devices preserves the order of events, which is what an engineer needs to reconstruct a failure.

The fourth result concerns the behavior of the client over time, including the situation in which the configuration service is unreachable. Figure 3 presents the lifecycle of a policy on the device as a set of states and transitions. A state diagram is used because the safety of the mechanism depends on what happens on each transition, and especially on the transitions caused by errors.




Figure 3. Lifecycle of a logging policy on the device with fail-safe transitions (compiled by the author based on [11, 12, 18, 19])

The lifecycle starts from a compiled baseline policy that records only errors and warnings into a small ring buffer, so a fresh installation is observable at a low level before any network request succeeds. A fetched policy passes validation of its signature, schema version and bounds before activation; a policy that fails validation is discarded, and the previous valid policy remains active. When the configuration service is unreachable, the client keeps the last valid policy only until its own expiration time and then returns to the baseline. Expiration is computed from the time of fetch on the device rather than from the server clock, so clock skew cannot extend a verbose policy. A remote kill switch revokes all non-baseline policies at once, which is the response to a suspected privacy issue or an unexpected cost.

The lifecycle formalizes the observation of Meinicke et al. [12] that feature flags are temporary by nature and that their removal is a persistent problem in practice. A diagnostic logging policy is an extreme case of a temporary flag: it is created to answer one question and loses its purpose once the question is answered. Encoding the expiry on the device ensures that forgotten policies do not continue to collect data. This design choice also limits the effect of the kind of correlated configuration errors that Mehta et al. [18] describe,

because any erroneous policy has a bounded lifetime even when nobody notices the error.

The fifth result addresses the protection of personal data. Evidence on how often personal data enters mobile logs is more extensive for the Android ecosystem than for iOS, where Lyons et al. [14] combined automated testing of applications with a crowdsourced collection of device logs. Figure 4 shows the prevalence of different types of personally identifiable information reported in that study. A chart is used because the distribution across types shows where the risk comes from, and this distribution is the argument for the design choices that follow.




Figure 4. Prevalence of personally identifiable information types detected in device logs in a crowdsourced study of 1,214 Android devices, % (compiled by the author based on [14])

Figure 4 shows that identifiers of the environment dominate: wireless network names and hardware addresses, Bluetooth device names and location appear far more often than directly entered data such as email addresses or phone numbers. Such values usually enter logs as context that a developer added to make a message informative, not as deliberate data collection. The same study reports that 95% of 76 applications using one analytics library set its logging level to DEBUG or above, although the library default was ERROR [14]. The lesson for remotely configurable logging is direct: if verbose levels are left enabled permanently, environmental context accumulates in logs; if the content of logs can be widened remotely, the risk grows unless redaction happens before the data leaves the instrumentation call.

The model therefore places privacy controls at three points. At the call site, each field carries a privacy class (public, internal identifier, personal), and personal fields are never uploaded in clear form; internal identifiers are replaced by keyed hashes whose salt rotates, so that sessions can be correlated within a diagnostic window but not linked over long periods. In the transport layer, an allowlist defines which fields of which categories may be uploaded under the current policy, and anything not on the list is dropped rather than scanned with patterns after the fact. In the control plane, approval of a policy that raises verbosity includes a privacy review, because the data collected under the policy must remain consistent with the privacy details that the application declares in the App Store. The study of Xiao et al. [15], in which 3,423 of 5,102 tested iOS applications had privacy labels inconsistent with their behavior, illustrates how easily declarations drift from practice when data collection changes independently of documentation. Aghili et al. [17] link the selection of attributes to anonymize with regulations such as the GDPR and the California Consumer Privacy Act, which applies directly to applications serving US users.

The sixth result concerns the cost of diagnostics on the device. The survey of Hort et al. [3] establishes energy, network usage, memory and responsiveness as the dimensions in which mobile applications are

optimized, and diagnostic logging consumes all four. The model expresses this cost as explicit budgets in the policy: a maximum number of bytes per session and per day, a maximum ring buffer size and a maximum share of time during which verbose capture may be active. Budgets are enforced on the device, and exceeding a budget downgrades the policy to the baseline for the rest of the period rather than failing silently.

Timing matters as much as volume. In the study of Cornejo et al. [22], which examined interactive desktop applications, users tolerated overhead differently depending on the type of operation: an overhead of up to about 30% was likely to be accepted for many operations, while noticeable slowdowns appeared in operations that users expect to be instantaneous. For a mobile client, this argues for moving formatting, compression and upload away from interaction-critical paths, such as scrolling, playback start or text input, and into idle periods or background transfers. Cândido et al. [4] also cite evidence of statistically significant differences in response time, battery consumption and CPU usage between mobile applications with logging enabled and disabled, which supports the conservative baseline used in the lifecycle.

Retroactive capture, discussed above, is the main tool for reconciling detail with cost. Detailed events stay in a memory ring buffer that is overwritten continuously, and only a trigger (an error, a stall, an abnormal termination detected at the next launch) causes the buffer to be persisted and scheduled for upload. In this way, the volume of uploaded data scales with the number of incidents rather than with the duration of use, which is the property that Zhang et al. [20] exploit for edge cases in distributed systems.

The seventh result connects the previous components in a form that a team can use during an investigation. Table 3 presents a decision matrix for six typical diagnostic situations in a large iOS application with media playback. For each situation it gives the recommended targeting, levels, capture mode, duration and upload condition. The matrix is given as a table because its purpose is to support quick, consistent decisions by different engineers.

Table 3. Decision matrix for typical diagnostic situations in a large iOS application (compiled by the author based on [3, 14, 19, 20, 22])

Situation	Targeting	Categories and level	Capture mode	Duration	Upload condition
A single user reports a failure through support	One installation, opt-in diagnostic session	All categories, debug	Streaming	Up to 24 hours	Any network, after user consent
Regression after a new application version	Small cohort of installations on the new version	Categories of changed modules, info	Ring buffer with error triggers	Until the fix is verified, capped by the client	Unmetered network
Playback stalls on unstable cellular networks	Small cohort on cellular networks	Playback and networking, debug	Ring buffer triggered by stall events	Several days	Unmetered network or charging
Performance degradation on older device models	Device class filter, small cohort	Performance intervals, info	Aggregated counters per session	One week	Background transfer
Suspected personal data in logs	All installations	Baseline only; affected category disabled	Kill switch; local queue purged	Until a corrected build is adopted	Uploads of the category suspended
Verification after a server-side fix	Previously affected cohort	Categories of the failing flow, info	Ring buffer	48 hours	Unmetered network

The matrix in Table 3 reflects a general rule: the narrower the question, the narrower the cohort and the shorter the policy. A single user who reports a problem through support can be given an opt-in diagnostic session with full verbosity for a short time, while a regression that affects a share of the audience is investigated with a small, stable cohort and only the categories related to the suspected component. The situation of a suspected privacy issue is handled not by collecting more data but by reducing collection everywhere through the kill switch, which demonstrates that the mechanism is also a tool for limiting data, not only for expanding it.

The reflective case of a large live streaming application with a multimillion audience was used to check whether the components of the model correspond to decisions that a real team has to take. Four considerations emerged from this comparison and are reported qualitatively.

The first consideration concerns the shared vocabulary of categories. In a large distributed iOS team, categories are created by many feature teams, and without a registry and naming convention they quickly duplicate one another. Treating the category registry as part of architecture review, in the same way as public module interfaces, keeps the set of categories understandable for engineers who later author policies. This corresponds to the naming convention and grouping practices identified by Mahdavi-Hezaveh et al. [11].

The second consideration concerns mixed code bases. The coexistence of Objective-C and Swift, and of UIKit and SwiftUI, documented in open-source applications by Baresi et al. [2], is also typical of long-lived commercial applications. A logging interface that is idiomatic only in Swift leaves legacy modules uninstrumented, so the interface has to be callable from both languages without loss of structure.

The third consideration concerns conservative defaults. Because the baseline policy is what the majority of devices run at any moment, its cost and content determine the everyday footprint of the mechanism. In practice, the discussion about which events belong to the baseline was more consequential than the discussion about verbose levels, which are applied briefly and to small cohorts.

The fourth consideration concerns ownership. A policy without a named owner and an expiration time is difficult to evaluate after the fact, because nobody can say whether it is still needed. Making these fields mandatory in the schema and enforcing expiry on the device, as described above, removes the need to rely on reminders.

On the basis of the results, the author formulates eight recommendations for teams that develop or audit diagnostic infrastructure for large iOS applications.

First, instrument once and control remotely: place structured logging points with categories and levels throughout the code base at build time and keep them disabled or at a low level by default, so that diagnostic requests do not require a release.

Second, make governance metadata mandatory: every policy carries an owner, a reason and an expiration time, and the client refuses policies without them.

Third, enforce safety on the client: compiled bounds on duration, volume and cohort size, validation of signatures and schema versions, and a return to the baseline when the configuration is unavailable beyond its expiry.

Fourth, sample cohorts, not events: select installations through stable hashed buckets and record complete sessions for them, so that the order of events is preserved.

Fifth, prefer retroactive capture: keep detailed events in a memory ring buffer and persist them only when a trigger indicates a problem.

Sixth, classify data at the call site: annotate each field with a privacy class, hash internal identifiers with rotating keys and upload only allowlisted fields.

Seventh, connect policy approval to privacy declarations: review verbose policies against the data practices that the application declares, and record the review in the audit log.

Eighth, expose the mechanism to staged, telemetry-guided rollout: increase the cohort of a policy in steps and let health signals stop it automatically, in the same way as for code changes in safe deployment systems.

These recommendations apply in full to applications with a large audience, a dedicated server infrastructure and several teams working on the client. For smaller applications, the same principles can be implemented

in a reduced form: a baseline policy, a single remotely controlled verbosity level and the diagnostic reports provided by the operating system often cover their needs. The model also assumes that a server channel for configuration exists; where configuration is already delivered for feature flags, the logging policy can share the same channel with a separate namespace and stricter validation.

Conclusion

The study set out to systematize the engineering requirements for remotely configurable client-side logging in large iOS applications and to propose a reference model that supports the decisions involved. Both parts of this aim have been achieved.

The analysis of the diagnostic loop showed that release-coupled diagnostics include stages, such as code changes, store review and update adoption, that remote configuration removes from the path of a diagnostic request, while adding a stage of policy approval that carries the governance burden. The integrative review of 22 sources identified three groups of findings that the design must reconcile: the unpredictability of diagnostic needs, the risks of runtime configuration and the costs of logging for the device and for user privacy.

On this basis the study proposed a four-layer reference architecture (instrumentation, on-device policy, transport and control plane), a configuration schema with defaults and client-enforced bounds, a policy lifecycle with fail-safe behavior under unavailable configuration and a decision matrix for six typical diagnostic situations. The reflective case confirmed that each component corresponds to a decision a large iOS team has to make, and it added practical considerations on category registries, mixed Swift and Objective-C code bases, conservative baseline policies and ownership of policies.

The hypothesis of the study is supported at the conceptual level: when the composition and verbosity of client logs are separated from the binary release and governed by expiration, budgets, privacy filters and fail-safe defaults, the diagnostic loop depends on configuration propagation and defect recurrence rather than on the release cycle, and the cost on the device is bounded by the policy rather than growing with verbosity. Quantitative confirmation of the size of these effects is a task for further empirical work, for example comparative measurements of time to diagnosis, energy use and data volume in applications that adopt the model.

The practical significance of the work lies in the eight recommendations and the artifacts (the schema, the lifecycle and the decision matrix), which iOS engineers, software architects, privacy specialists and engineering managers can use when they design, review or audit diagnostic infrastructure for mobile applications.

References

1. Burley, J., & Fradkin, A. (2025). The Apple ecosystem in the US: An overview of the App Store marketplace and its growth [Report]. Analysis Group. https://www.apple.com/newsroom/pdfs/2024-US-Apple-Ecosystem-Report.pdf
2. Baresi, L., Di Penta, M., Quattrocchi, G., & Tamburri, D. A. (2024). How have iOS development technologies changed over time? A study in open-source. In Proceedings of the IEEE/ACM 11th International Conference on Mobile Software Engineering and Systems (MOBILESoft '24) (pp. 33-42). ACM. https://doi.org/10.1145/3647632.3647988
3. Hort, M., Kechagia, M., Sarro, F., & Harman, M. (2022). A survey of performance optimization for mobile applications. IEEE Transactions on Software Engineering, 48(8), 2879-2904. https://doi.org/10.1109/TSE.2021.3071193
4. Cândido, J., Aniche, M., & van Deursen, A. (2021). Log-based software monitoring: A systematic mapping study. PeerJ Computer Science, 7, Article e489. https://doi.org/10.7717/peerj-cs.489
5. Chen, B., & Jiang, Z. M. (2021). A survey of software log instrumentation. ACM Computing Surveys, 54(4), Article 90. https://doi.org/10.1145/3448976
6. He, S., He, P., Chen, Z., Yang, T., Su, Y., & Lyu, M. R. (2021). A survey on automated log analysis for reliability engineering. ACM Computing Surveys, 54(6), 1-37. https://doi.org/10.1145/3460345
7. Usman, M., Ferlin, S., Brunstrom, A., & Taheri, J. (2022). A survey on observability of distributed edge &

container-based microservices. IEEE Access, 10, 86904-86919. https://doi.org/10.1109/ACCESS.2022.3193102

8. Gomes, F., Rego, P., & Trinta, F. (2025). A systematic mapping study on observability of microservices-based applications: Fundamentals, classifications, and challenges. Computing, 107(9), Article 183. https://doi.org/10.1007/s00607-025-01540-w

9. Harty, J., Zhang, H., Wei, L., Pascarella, L., Aniche, M., & Shang, W. (2021). Logging practices with mobile analytics: An empirical study on Firebase. In 2021 IEEE/ACM 8th International Conference on Mobile Software Engineering and Systems (MobileSoft) (pp. 56-60). IEEE. https://doi.org/10.1109/MobileSoft52590.2021.00013

10. Johnson, J., Mahmud, J., Wendland, T., Moran, K., Rubin, J., & Fazzini, M. (2022). An empirical investigation into the reproduction of bug reports for Android apps. In 2022 IEEE International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE. https://doi.org/10.1109/SANER53432.2022.00048

11. Mahdavi-Hezaveh, R., Dremann, J., & Williams, L. (2021). Software development with feature toggles: Practices used by practitioners. Empirical Software Engineering, 26(1), Article 1. https://doi.org/10.1007/s10664-020-09901-z

12. Meinicke, J., Wong, C.-P., Vasilescu, B., & Kästner, C. (2020). Exploring differences and commonalities between feature flags and configuration options. In Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP '20) (pp. 233-242). ACM. https://doi.org/10.1145/3377813.3381366

13. Rahman, T. (2023). Feature toggle usage patterns: A case study on Google Chromium. In 2023 IEEE/ACM 20th International Conference on Mining Software Repositories (MSR) (pp. 142-147). IEEE.

14. Lyons, A., Gamba, J., Shawaga, A., Reardon, J., Tapiador, J., Egelman, S., & Vallina-Rodriguez, N. (2023). Log: It's big, it's heavy, it's filled with personal data! Measuring the logging of sensitive information in the Android ecosystem. In Proceedings of the 32nd USENIX Security Symposium (pp. 2115-2132). USENIX Association. https://www.usenix.org/conference/usenixsecurity23/presentation/lyons

15. Xiao, Y., Li, Z., Qin, Y., Bai, X., Guan, J., Liao, X., & Xing, L. (2023). Lalaine: Measuring and characterizing non-compliance of Apple privacy labels. In Proceedings of the 32nd USENIX Security Symposium (pp. 1091-1108). USENIX Association. https://www.usenix.org/conference/usenixsecurity23/presentation/xiaoyue

16. Kollnig, K., Shuba, A., Van Kleek, M., Binns, R., & Shadbolt, N. (2022). Goodbye tracking? Impact of iOS App Tracking Transparency and privacy labels. In Proceedings of the 2022 ACM Conference on Fairness, Accountability, and Transparency (FAccT '22) (pp. 508-520). ACM. https://doi.org/10.1145/3531146.3533116

17. Aghili, R., Li, H., & Khomh, F. (2025). Protecting privacy in software logs: What should be anonymized? Proceedings of the ACM on Software Engineering, 2(FSE), 1317-1338. https://doi.org/10.1145/3715779

18. Mehta, S., Bhagwan, R., Kumar, R., Bansal, C., Maddila, C., Ashok, B., Asthana, S., Bird, C., & Kumar, A. (2020). Rex: Preventing bugs and misconfiguration in large services using correlated change analysis. In 17th USENIX Symposium on Networked Systems Design and Implementation (NSDI '20) (pp. 435-448). USENIX Association. https://www.usenix.org/conference/nsdi20/presentation/mehta

19. Li, Z., Cheng, Q., Hsieh, K., Dang, Y., Huang, P., Singh, P., Yang, X., Lin, Q., Wu, Y., Levy, S., & Chintalapati, M. (2020). Gandalf: An intelligent, end-to-end analytics service for safe deployment in large-scale cloud infrastructure. In 17th USENIX Symposium on Networked Systems Design and Implementation (NSDI '20) (pp. 389-402). USENIX Association. https://www.usenix.org/conference/nsdi20/presentation/li

20. Zhang, L., Xie, Z., Anand, V., Vigfusson, Y., & Mace, J. (2023). The benefit of hindsight: Tracing edge-cases in distributed systems. In 20th USENIX Symposium on Networked Systems Design and Implementation (NSDI '23) (pp. 321-339). USENIX Association. https://www.usenix.org/conference/nsdi23/presentation/zhang-lei

21. Reichelt, D. G., Bulej, L., Jung, R., & van Hoorn, A. (2024). Overhead comparison of instrumentation

frameworks. In Companion of the 15th ACM/SPEC International Conference on Performance Engineering (ICPE '24 Companion) (pp. 249-256). ACM. https://doi.org/10.1145/3629527.3652269

22. Cornejo, O., Briola, D., Micucci, D., & Mariani, L. (2020). In-the-field monitoring of functional calls: Is it feasible? Journal of Systems and Software, 163, Article 110523. https://doi.org/10.1016/j.jss.2020.110523